

# Storage location of data

All user-specific data, QV configuration settings, licence data, databases etc. are stored in a central folder of your harddisk. By default, during a new program installation, the following destination will be appointed:

## **Common Documents\QV7\_Data**

If you were upgrading from QV6, this folder will remain:

## **Common Documents\QV6\_Data**

or even, if you were coming from TTQV5:

## **Common Documents\TTQV5\_Data**

In the following your data-file will be described as QV\_Data.

In this QV\_Data folder you will find at least the following subdirectories:

_lic	This is the location of the licence file which you should backup from time to time and which you will need in case you have to reinstall QV. By simply restoring this *.lic file at its original place you can reactivate your QV software including all your maps without the need to activate every module once again!
Qu5	Here you will find all databases from the folder QV_Data in the X-Plorer under the identical file name and the extension *.qv5db.
System	Here you will find all databases from the folder System in the X-Plorer under the identical file name and the extension *.qv5db.
Import, Export	These are the default folders for data import and export.
Odb	This is the default folder for the geographic databases.
Screenshots	This is the default folder for the QV screenshot function.

Of course, you can create additional subdirectories in this folder.

## **It is highly recommended to make backup copies of this QV\_Data folder on a regular basis!**

If you like to shift this folder to another drive, manual editing of the Windows registry is required. Therefore we generally do not recommend to do so.

Experienced users can proceed as follows (example for Windows-XP):

- Terminate QuoVadis and make a backup copy of the folder QV\_Data
- Create the folder in which you would like to have your QV data stored, e.g. D:\QVData
- Copy all files from QV\_Data to this folder, e.g. to D:\QVData.
- Start the program **regedit**
- Search the **HKEY\_LOCAL\_MACHINE\SOFTWARE\QuoVadis\7** section and the **dir\_mydata** key and specify the path; - in this case D:\QVData\). This folder will be valid for all users on this PC.
- In case you want different paths for various users, login with the corresponding user name and enter the new path in the section **HKEY\_CURRENT\_USER\Software\QuoVadis\7** within the key **dir\_mydata**

During start-up, QV will first refer to *HKEY\_CURRENT\_USER\Software\QuoVadis\7\dir\_mydata*. If existing and valid, this folder will be used. If not, the path *HKEY\_LOCAL\_MACHINE\SOFTWARE\QuoVadis\7\dir\_mydata* will be checked. If this one is also not valid, QV won't start.

Attention: with other versions of MS-Windows the registry key to be edited may be a different one, example with Win7-64:

**[HKEY\_LOCAL\_MACHINE\SOFTWARE\Wow6432Node\QuoVadis\7]**

From:

<https://quovadis-gps.com/anleitungen/quovadis-7/> - QuoVadis 7 GPS Software Wiki

Permanent link:

[https://quovadis-gps.com/anleitungen/quovadis-7/doku.php?id=en:10\\_install:e\\_datapath](https://quovadis-gps.com/anleitungen/quovadis-7/doku.php?id=en:10_install:e_datapath)

Last update: **2013/09/26 14:44**

